

### Enterprise, High Performance and Video Processing

Benefit from scalable storage performance and video processing with the XX-B-ENT4 server. This 2U, 2-socket platform brings you scalability and performance to adapt to a variety of video surveillance applications. Up to 168TB of raw storage is provided by (12) 24/7 duty cycle SATA drives. Paired with the latest Intel® Xeon® Scalable processor, this provides high-density storage with enterprise throughput for the most demanding applications.

Ease of operation is provided with dual OS SSDs for accelerated boot and application load times. Remote management, provided by iDRAC, allows for constant system status and critical resource monitoring. RAID 6 storage options, in addition to redundant 750W power supplies, provide system high availability while a five-year, on-site, next business day, Keep Your Hard Drive warranty guarantees peace of mind.

### KEY FEATURES

- Up to 168TB of Raw Storage
- Intel® Xeon® Silver 4110 Scalable Processor
- Operating System: Windows Server 2016
- iDRAC features include:
  - Remote Management
  - Disaster Recovery
  - Critical Resource Monitoring



**SSD & 24/7 Duty Cycle SATA Drives**




**Redundant Power**



**RAID 6**



**5-Year, On-site, NBD,  
Keep Your Hard Drive Warranty**



Back

— POWERED BY —  
**DELL EMC**

**FOR MORE INFORMATION:** [enexxis.com](http://enexxis.com) | [info@enexxis.com](mailto:info@enexxis.com) | +1.215.322.8400

Copyright © 2019, Enexxis. All rights reserved. This document is provided for information purposes only. The contents are subject to change without notice.

SYSTEM	
<b>Processor(s)</b>	Intel® Xeon® Silver 4110 Scalable Processor (8 Cores, 16 Threads, 2.1GHz)
<b>Processor Passmark</b>	Intel® Xeon® Silver 4110: 12,020
<b>Maximum Storage</b>	Up to 168 TB
<b>Operating System</b>	Windows Server 2016
<b>Memory</b>	Single Processor: 16GB (2x 8GB)
<b>RAID</b>	OS RAID 1; Data RAID 6
<b>RAID Controller</b>	PERC H740P (8GB NV Cache, Supports RAID 0, 1, 5, 6, 10)
<b>Networking</b>	(2) 1GbE RJ45 Ports
<b>Expansion Slots</b>	(1) x16 full-height, (2) x8 low profile PCIe slots (in default configuration)
<b>USB(s)</b>	Rear (2) USB 3.0, Front (2) USB 2.0, Internal (1) USB 3.0
<b>Video Outputs</b>	(1) VGA
<b>Remote Management</b>	iDRAC Basic
<b>Manufacturer</b>	Enexxis
<b>Warranty</b>	5-Year, On-site, NBD, Keep Your Hard Drive Warranty
MECHANICAL	
<b>Form Factor</b>	2U Rackmount
<b>Rack Support</b>	Sliding Rack Rail with Cable Management Arm
<b>Hard Drive Bays</b>	(12) 3.5" Hot Swappable Bays & (2) M.2 SSD Slots
<b>Hard Drives Supported</b>	PCIe NVMe & SATA
<b>Power Supply(s)</b>	(2) 750W (100-240VAC) 80 Plus Platinum
<b>Maximum Power Draw</b>	750W
<b>Operating Temperature</b>	(Min) 50°F - (Max) 95° F [(Min) 10°C - (Max) 35° C]
<b>Operating Humidity</b>	5 ~ 90% (non-condensing)
<b>Dimensions (WxDxH)</b>	19" (482.6mm) x 28.15" (646mm) x 3.4" (86.8mm)
<b>Max. Weight</b>	65.43 lbs. (29.68 kg)

